

T.I.S.

PN 10 Art. C087 TIS

PN 16 Art. C086 TIS

VALVOLA DI RITEGNO ASSIALE PN10/16



AXIAL DISC CHECK VALVE PN10/16

APPLICAZIONE:

Stazioni di pompaggio per acqua, irrigazione e depurazione acque.

APPLICATION:

Pumping stations and networks for clean water distribution, irrigation and water treatment.



NORMA PROGETTO:	EN 1074-3
FLANGE:	EN 1092-2
COLLAUDI:	EN 12266-1
TEMP. ESERCIZIO:	Max. +70°C
CONTROPRESSIONE:	Min. 0,3 bar
DESIGN STANDARD:	EN 1074-3
FLANGES:	EN 1092-2
TESTS:	EN 12266-1
WORKING TEMP.:	Max. +70°C
BACKPRESSURE:	Min. 0,3 bar

DENOMINAZIONE PART	MATERIALI MATERIALS
1 CORPO BODY	EN-GJL 250 EN-GJL 250
2 DISCO DISC	EN-GJS 400-15 EN-GJS 400-15
3 GUARNIZIONE SEAL	EPDM EPDM
4 MOLLA SPRING	ACCIAIO INOX STAINLESS STEEL
5 GUIDA GUIDE	OTTONE BRASS
6 GUIDA GUIDE	EN-GJS 400-15 EN-GJS 400-15

RIVESTIMENTO ESTERNO/INTERNO: Polvere epossidica di colore blu RAL5017 con spessore 200µm.

SURFACE PROTECTION: FBE coating process with epoxy resin powder of blue colour RAL5017 and thickness of 200µm.

DN	G	K		D		n-ød		b		L	W(kg)
		PN10	PN16	PN10	PN16	PN10	PN16	PN10	PN16		
50	98	125	125	165	165	4-19	4-19	20	20	100	5.7
65	118	145	145	185	185	4-19	4-19	20	20	120	8.7
80	132	160	160	200	200	8-19	8-19	22	22	140	10.8
100	156	180	180	220	220	8-19	8-19	24	24	170	13.5
125	184	210	210	250	250	8-19	8-19	26	26	200	21
150	211	240	240	285	285	8-23	8-23	26	26	230	30
200	260	295	295	340	340	8-23	12-23	26	30	300	49
250	319	350	355	405	405	12-23	12-28	28	32	370	73.3
300	370	400	410	460	460	12-23	12-28	28	32	410	90